

## Seat Belt for Forklifts

Forklift Seat Belt - This guideline reason is to describe the Regulation necessities for the utilization of operator restraints or seatbelts on forklifts. It is the employers' liability to make sure that each and every machinery, piece of equipment and tool within the workplace is chosen and utilized correctly and worked in accordance with the manufacturer's instructions.

Rough Terrain lift trucks must meet the guidelines of ANSI Standard ASME B56.6-1992 with regards to their design, maintenance, inspection, fabrication and use.

Side boom tractors and mobile machine with a Rollover Protective Structure, or ROPS for short, have to include seat belts which meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machinery has seat belts required by law, the driver and subsequent passengers need to make certain they use the belts every time the vehicle is in motion or engaged in operation as this can cause the machinery to become unstable and therefore, not safe.

When a seat belt or various driver restraint is required on a forklift.

While working a forklift, the seat belt requirements would depend on some factors. Contributing factors to this determination might include whether or not the the forklift is outfitted with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was made. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to an operator restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to aid the operator in reducing the chance of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device could comprise a seat belt, although a seat belt is not essentially a part of such machine or system.